

DX kozijn stomp model 03 Vierkant Luxe S 55 mm



Deurmaat			Kozijnspoonningmaat		Kozijnmaat		Wandopening				Vrije doorgang		Kozijn bekledingsmaat	
h1	b1a	b1b	h6	b6	h5	b5	h3 min	h3 max	b3 min	b3 max	h7	b7	h2	b2
			h1+6	b1a+b1b-4	h1+19	b1a+b1b+18	h1+27	h1+52	b1a+b1b+38	b1a+b1b+88	h1-5	b1a+b1b-26	h1+61	b1a+b1b+106
2015	630	630	2021	1256	2032	1278	2042	2067	1298	1348	2010	1234	2076	1366
2015	680	680	2021	1356	2032	1378	2042	2067	1398	1448	2010	1334	2076	1466
2015	730	730	2021	1456	2032	1478	2042	2067	1498	1548	2010	1434	2076	1566
2015	780	780	2021	1556	2032	1578	2042	2067	1598	1648	2010	1534	2076	1666
2015	830	830	2021	1656	2032	1678	2042	2067	1698	1748	2010	1634	2076	1766
2015	880	880	2021	1756	2032	1778	2042	2067	1798	1848	2010	1734	2076	1866
2015	930	930	2021	1856	2032	1878	2042	2067	1898	1948	2010	1834	2076	1966

* Draainaden links /rechts : 3 mm
* Draainaad boven : 2 mm
* Ruimte onder de deur: 4 mm

Wandopening h3=h1 + 32
b3=b1a + b1b + 48

Vrije doorgang h7=h1- 5
b7=b1a + b1b - 26

Kozijnbekledingsmaat h2=h1+ 61
b2=b1a + b1b + 106



BAV = Bovenkant Afgewerkte Vloer